PRODUCT INSTALLATION GUIDELINES

TYVEK® HOMEWRAP

Important notes:

- Tyvek® HomeWrap is not designed to withstand prolonged weathering, hence the external cladding should be applied within 2 months of
 installation.
- Tyvek® HomeWrap must not be installed in areas where winds exceed 120kph.
- Tyvek® HomeWrap shall be installed in accordance with 'AS/NZS 4200.2:1994 Pliable Building Membranes and Underlays Installation Requirements for Metal Roofs, Tile Roofs and Walls'.
- Tyvek® HomeWrap should not be used under roofs. Due to the lightweight nature of the product, wind may cause excessive flapping and noise.

Framed walls:

Tyvek® HomeWrap is to be fixed securely to the frame using tool fasteners. Fixing points shall be at 600mm spacings horizontally and 600mm spacings vertically. Alternatively, Tyvek® HomeWrap may be fixed using staples and by strapping at 600mm spacings.

Note: if your project requirements vary to the application/installation guidelines provided, contact Fletcher Insulation for advice prior to commencing the installation.

© Fletcher Insulation Pty Limited 2016. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. Tyvek® is a trademark and registered trademark of E.I. du Pont de Nemors and Company. Unless otherwise stated all ™ and ® are trademarks and registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355.

IG5_Revision_0_Issue Date 18032016



Building Better, Together.

1300 654 444