

Date of issue: 31.01.2020

FI Mineral Wool Insulation

Section 1: Identification of the Material and Supplier

Product name	FI Mineral Wool Products
Other names:	Fire Stop Party Wall Batts Fireseal Fire strip
Recommended use:	Thermal and acoustic insulation including energy conservation, used in homes, public and commercial buildings, warehouses, industrial and petrochemical plants, motor vehicles, ships, public transport, power stations and white goods.
Supplier:	Fletcher Insulation Pty Ltd
Address:	600 Woodstock Ave, Rooty Hill NSW 2766
Telephone:	1300 654 444
Emergency contact:	1300 654 444 or Poisons Information Centre 13 11 26 (Australia Wide)
Website:	www.insulation.com.au
Important notice:	As FI Mineral wool manufactured or sold in Australia and New Zealand by Fletcher Insulation is classified as non-hazardous , a Safety Data Sheet (SDS) is not strictly required under Australian Regulations. As such, this Safety Use Information Sheet (SUIS) is issued by Fletcher Insulation for the information of users, installers and the community. It has been formatted in accordance with the Code on Preparation of a Safety Data Sheets for hazardous chemicals, December 2011, Safe Work Australia. The information in this SUIS must not be altered, deleted or added to. The Supplier will not accept any responsibility for any changes made to its SUIS by any other person or organization. The Supplier will issue a new SUIS when there is a change in product specifications and/or ASCC standards, codes, guidelines, or Regulations.

Section 2: Hazards Identification

Non-hazardous substance/non-dangerous goods

Not classified as hazardous according to the criteria of Safe Work Australia.

Hazards:	Not applicable
Risk phrases:	Not applicable
Safety phrases:	S36/37/39 – Wear suitable protective clothing, gloves and eye/face protection.

Section 3: Composition/Information on Ingredients

Ingredient (common name)	Proportion	CAS Number
Slag wool fibre	> 95%	65997-17-3
Phenolic resin	< 5%	9003-35-4
If laminated, contains the following adhesive		
Vinyl alcohol polymer	< 1%	9002-89-5

Section 4: First Aid Measures

Inhalation:	If exposed to excessive levels of dust, leave area of dust exposure and remain away until coughing and other symptoms subside. Other measures are usually not necessary. Seek medical attention if symptoms persist.
Ingestion:	Rinse mouth and drink water. Never give anything by mouth to an unconscious person. Seek medical attention if symptoms occur.
Skin:	In case of skin contact rinse with cool water and then wash affected areas with soap and warm water. Mechanical action of fibres on skin can cause itchiness. A commercially available skin cream or lotion may be helpful to treat dry skin areas. Seek medical attention if symptoms persist.
Eyes:	In case of eye contact, immediately irrigate eyes with plenty of running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention. Contact lenses should not be worn when handling this product.

Section 5: Fire Fighting Measures

For major fires call the Fire Brigade. Ensure that an escape path is available from any fire.

Fire fighting procedures:	For major fires call the Fire Brigade. Ensure that an escape path is available from any fire.
Suitable extinguishing media:	Carbon dioxide (CO ₂), water, water fog, foam and dry chemical.
Hazardous decomposition products:	Oxides of carbon and smoke.
Firefighting equipment:	Wear Safe Work Australia approved self-contained breathing apparatus and full protective clothing.
Unusual fire or explosion hazards:	The products are non-combustible and do not pose a fire hazard. However, packaging material may burn.
Hazchem Code:	Not allocated.

Section 6: Accidental Release Measures

Containment and clean up procedure:	Wear appropriate personal protective equipment such as gloves, protective clothing. Pick up large pieces. Clean area using wet sweep methods to avoid dispersion of any irritant fibres or approved micro filter equipped vacuum cleaner. These procedures will help minimise potential exposures. Place in a sealable plastic bag for disposal according to applicable local and state government regulations. Never use compressed air and avoid dry sweeping.
-------------------------------------	--

Section 7: Handling and Storage

Handling:	Use of safe work practices are recommended to avoid eye or skin contact, inhalation or ingestion. Observe good personal hygiene. Keep work area clean of dust and fibres by using an industrial vacuum cleaner with high efficiency filter or wetting down area with water. Never use compressed air and avoid dry sweeping.
Storage:	Material should be kept dry and protected from the elements. Protect from physical damage.

Section 8: Exposure Controls/Personal Protection

Exposure standards (Safe Work Australia):	Slag wool fibre (man-made mineral fibre) – respirable fibres: TWA: 2mg/m ³
Material data:	Generally, not applicable.
Engineering controls:	Local exhaust ventilation is recommended when dusts can be released in excess of established airborne exposure limits. If cutting or trimming with power equipment, dust collectors and local ventilation should be used. Keep work area clean of dust and fibres by using an industrial vacuum cleaner with high efficiency filter or wetting down area with water. Never use compressed air and avoid dry sweeping.
Personal protection	
Respiratory protection:	Wear an approved dust respirator in poorly ventilated areas where local exhaust is not feasible, if TLV is exceeded, and/or when dusty conditions exist. See Australian Standards AS/NZS 1715 and 1716 for more information.
Eye protection:	Wear safety glasses with side shields or goggles to avoid eye irritation. See Australian Standards AS 1336 and AS/NZS 1337 for more information.
Skin protection:	Direct skin contact can be minimised by wearing long sleeved shirts and long trousers, a cap or hat, and standard duty gloves. See Australian Standards AS2161 and 2919 and AS/NZS 2210 for more information.
Hygiene practices:	Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Work clothes should be washed regularly and separately from other clothes before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Section 9: Physical and Chemical Properties

Appearance:	Tan or off-yellow solid
Physical properties:	Batt or roll of mineral fibres
Odour:	Low odour
Melting range:	1150°C
Boiling range:	Not applicable
Decomposition temperature:	Not applicable
Volatile component (% vol):	Not applicable
Solubility in water (g/L):	Insoluble
pH (as supplied)	Not applicable

Section 10: Stability and Reactivity

Chemical stability:	Stable under normal conditions of use.
Incompatible materials:	Acids – gives off hydrogen sulfide (H ₂ S) under certain acidic conditions.
Hazardous decomposition products:	Oxides of carbon and smoke would be produced at high temperatures with thermal decomposition.
Hazardous polymerisation:	Will not occur
Conditions to avoid:	Physical damage

Section 11: Toxicological Information

Toxicity:	Phenolic resin: Harmful if swallowed or inhaled. May be harmful in contact with the skin. Toxicity may depend upon extent of polymerisation and the degree to which unreacted monomer is present, since both monomers are toxic (formaldehyde and phenol).
Routes of exposure:	Inhalation, ingestion, eye and skin.
Acute health effects:	
Inhalation:	May cause irritation of the nose, throat and upper respiratory tract resulting in coughing, sneezing and nasal irritation.
Ingestion:	Unlikely under normal conditions of use. No known effects.
Eye:	May cause eye discomfort resulting in watering and redness.
Skin:	May irritate the skin resulting in itching and occasionally a red rash which usually disappears quickly.
Chronic health effects:	No information available
Existing conditions aggravated by exposure:	Pre-existing upper respiratory and lung disease such as, but not limited to, bronchitis, emphysema and asthma. Persons with chronic or systemic skin or eye disease should use precautions and wear all personal protective equipment when working with this product.
Carcinogenicity:	Mineral wool fibres are classified as IARC Group 3 – Non-classifiable as to its carcinogenicity to humans.

Section 12: Ecological Information

Ecotoxicity:	This product is not expected to have an adverse effect on the ecology.
Mobility:	No information available.

Section 13: Disposal Considerations

Disposal methods and containers:	Dispose according to applicable local and state government regulations.
Special precautions for landfill or incineration:	Please consult your state Land Waste Management Authority for more information.

Section 14: Transportation Information

Transport requirements:	Not regulated for transport of dangerous goods: ADG7, UN, IATA, IMDG
Hazchem code:	Not applicable

Section 15: Regulatory Information

Slag wool fibre, phenolic resin and vinyl alcohol polymer are listed in the Australian Inventory of Chemical Substances (AICS).

Poisons Schedule:	None
Poisons Information Centre	13 11 26 (Australia Wide)

Section 16: Other Information

Additional Information and Reference Documents

Poisons Information Centre 13 11 26 (Australia Wide)

Please read instructions/label before using product.

Code on Preparation of a Safety Data Sheets for hazardous chemicals, December 2011, Safe Work Australia.

Australian Standards References:

AS/NZS 1336 Eye and Face Protection Guidelines

AS/NZS 1715 Selection, Use and Maintenance of Respiratory Protective Equipment

AS/NZS 1716 Respiratory Protective Devices

AS/NZS 2161 Occupational Protective Gloves Selection, Use and Maintenance

AS2919 Industrial Clothing

AS/NZS 2210 Occupational Protective Footwear

Abbreviations used:

IARC: International Agency for Research on Cancer

NTP: National Toxicology Program (U.S.)

OSHA: Occupational Safety and Health Administration (U.S.)

STEL: Short term exposure limit

TWA: Time weighted average

Prepared by: 4cRisk.com.au Pty Ltd

This SUIIS was correct at the time it was prepared (see below for the date). The Supplier, as part of its Health and Safety Programme, updates SUIIS when its ongoing review process indicates a need for a change to be made. You should make sure that the SUIIS you are reading and relying on is current. You can do this by contacting the Supplier at the above address.

Issue Date:	31 January 2020
Revision:	0
Supersedes:	MSDS06_Revision_0_Issue Date 01032016
Reason for issue:	Update

© Fletcher Insulation Pty Limited 2019. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. Unless otherwise stated those trade marks followed by ® are registered trade marks and those followed by ™ are trade marks of Fletcher Insulation Pty Ltd ACN 001 175 355, a member of the Fletcher Building Group. SUIIS06_Revision_0_Issue Date 310120.

For more information call 1300 654 444
email info@insulation.com.au or web www.insulation.com.au

Fletcher
Insulation
Building Better, Together