FIRMASoft® Perfectly Balanced

Insulation for Australian homes. Soft to Handle + Firm to Fit.



FirmaSoft® Wall and Ceiling insulation batts are perfectly balanced – soft and comfortable to handle, with a firm fit for easy installation and superior thermal and acoustic performance.

Soft to handle

Stay firmly in place

- Made in Australia
- Up to 80% recycled content
- Low dust formula
 No
- Non-combustible



insulation.com.au



FirmaSoft[®] insulation batts by Fletcher Insulation have been designed and manufactured to combine the perfect balance between softness and firmness.




They are soft to handle, yet fit firm in place, ensuring installation is a breeze, while providing maximum long-term performance.

Manufactured in Australia using a low dust formula and up to 80% recycled content, **FirmaSoft®** batts will help improve the energy efficiency and comfort within the home. And you'll have peace of mind knowing they come with a lifetime performance warranty.

FirmaSoft[®] is ideal for DIY and builders, making insulating a home easier than ever before.

Firm fitting for superior performance



Wall

Ceiling

FirmaSoft® internal and external wall insulation

High thermal performance + effective noise reduction

- Soft to handle and fits firmly in place
- Made in Australia

| - Made III Adstralia | | | | | | | | | | |
|--|-----------------|-------------|--------------|----------------|-------------------|-------------------------------------|-----------------|--|--|--|
| Material R-value m ² K/W | Thickness mm | Width mm | Length mm | m² per pack | Batts per pack | Coverage per pack m ² | Product Code | | | |
| R1.5 | 70 | 430 | 1160 | 11.0 | 22 | 12.4 | 900281 | | | |
| | | 580 | | 14.8 | 22 | 16.9 | 900280 | | | |
| R2.0 | 90 | 430 | 1160 | 11.0 | 22 | 12.4 | 900282 | | | |
| | | 580 | | 12.1 | 18 | 13.8 | 900283 | | | |
| R2.5HD | 90 | 430 | 1160 | 6.0 | 12 | 6.8 | 900292 | | | |
| | | 580 | | 8.1 | 12 | 9.1 | 900293 | | | |

FirmaSoft® ceiling insulation

High thermal performance + effective noise reduction

Soft to handle and fits firmly in place

Made in Australia

| Material R-value m ² K/W | Thickness mm | Width mm | Length mm | m² per pack | Batts per pack | Coverage per pack m ² | Product Code | | | |
|--|-----------------|-------------|--------------|----------------|-------------------|-------------------------------------|-----------------|--|--|--|
| R3.5 | 175 | 430 | 1160 | 8.0 | 16 | 9.0 | 900286 | | | |
| | | 580 | | 6.7 | 10 | 7.6 | 900287 | | | |
| R4.1 | 215 | 430 | 1160 | 5.0 | 10 | 5.6 | 900288 | | | |
| | | 580 | | 6.7 | 10 | 7.6 | 900289 | | | |
| R5.0 | 220 | 430 | 1160 | 4.0 | 8 | 4.5 | 900290 | | | |
| | | 580 | | 5.4 | 8 | 6.1 | 900291 | | | |

© Fletcher Insulation Pty Limited, 2023. The information contained within this bulletin is intended as a guide for information only and is subject to change without notice. Fletcher Insulation does not invite any person to act or rely upon such information. Before application in a particular situation, Fletcher Insulation recommends that you obtain appropriate independent qualified expert advice confirming the suitability of product(s) and information in question for the application proposed. To the extent permitted by law, Fletcher Insulation disclaims all liability (including liability for all loss and damage resulting from the direct or indirect use, or reliance on, the information provided in this bulletin. ™ and ® are registered trademark of Fletcher Insulation Pty Limited ACN 001 175 355, a member of the Fletcher Building Group. BR030-Revision_3_Issue Date 13042023.





