

Sisalkraft® 350

Section 1: Identification of the Material and Supplier

Product name	Sisalkraft® 350
Recommended use:	Vapour seal tape in residential, commercial and HVAC applications.
Supplier:	Fletcher Insulation Pty Ltd
Address:	127 Frankston-Dandenong Road, Dandenong South, VIC 3175
Telephone:	1300 654 444
Emergency contact:	1300 654 444
Website:	www.insulation.com.au
Important notice:	As Sisalkraft® 350 manufactured or sold in Australia and New Zealand by Fletcher Insulation is classified as non-hazardous , a Safety Data Sheet (SDS) is not strictly required under Australian Regulations. As such, this Safety Use Information Sheet (SUIS) is issued by Fletcher Insulation for the information of users, installers and the community. It has been formatted in accordance with the Code on Preparation of a Safety Data Sheets for hazardous chemicals, December 2011, Safe Work Australia. The information in this SUIIS must not be altered, deleted or added to. The Supplier will not accept any responsibility for any changes made to its SUIIS by any other person or organization. The Supplier will issue a new SUIIS when there is a change in product specifications and/or ASCC standards, codes, guidelines, or regulations.

Section 2: Hazards Identification

Non-hazardous substance/Non-dangerous goods

Not classified as hazardous according to the criteria of Safe Work Australia.

Section 3: Composition/Information on Ingredients

Ingredient (common name)	Proportion	CAS Number
Kraft Paper	60–90%	
Chlorinated hydrocarbons	< 10%	
Antimony trioxide	< 10%	1309-64-4
Glass filament	< 10%	

Section 4: First Aid Measures

The following relate to treatment of any irritant health effects resulting from exposure to any dust or the fumes evolved if product is heated to above 120°C.

Inhalation:	Remove to fresh air. If symptoms persist seek medical attention.
Ingestion:	Unlikely under normal conditions of use. Rinse the lips and mouth with water, give water to drink, and seek medical attention.
Skin:	Sluice with water and, if irritation persists, seek medical attention.
Eyes:	Flush with copious amounts of water. If symptoms persist seek medical attention.

Section 5: Fire Fighting Measures

For major fires call the Fire Brigade. Ensure that an escape path is available from any fire.

Specific hazards:	Will burn if involved in a fire. Delamination may occur at temperatures over 80°C.
Fire fighting procedures:	If product is present in a fire, toxic fumes may be evolved. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Firefighters wear full protective equipment including Self Contained Breathing Apparatus (SCBA) according to fire conditions.
Suitable extinguishing media:	Use extinguishing media (e.g. carbon dioxide, water, foam or dry chemical) and equipment as required by fire in surrounding materials.
Hazardous combustion products:	Chlorine and hydrogen chlorine may be evolved if product is heated to above 120°C.
Fire fighting equipment:	Wear Safe Work Australia approved self-contained breathing apparatus and full protective clothing.
Hazchem Code:	Not allocated

Section 6: Accidental Release Measures

Containment and clean up procedure:	Reuse where possible or place in a sealable plastic bag for disposal according to local authority guidelines.
-------------------------------------	---

Section 7: Handling and Storage

Handling:	As supplied and once installed, does not release dust, and does not cause any health effects.
Storage:	Store in sealed container in cool, dry area. Ensure packages are adequately labelled, protected from physical damage, and sealed when not in use.

Section 8: Exposure Controls/Personal Protection

Exposure Standards (Safe Work Australia):	<p>Safe Work Australia recommends the following Time Weighted Averages (TWA) to dust from the product or to fumes from high temperature decomposition:</p> <ul style="list-style-type: none"> - Chlorine: 3mg/m³ - Hydrogen Chloride: 7.5 mg/m³ - Antimony Trioxide: 0.5mg/m³ <p>Safe Work Australia standards provide that all exposures should be kept as low as practicable. Total dust (of any type, or particle size): 10 mg/m³ TWA.</p> <p>In typical installation conditions or where work is being done on insulated premises, a variety of dusts may be present. In any work area where almost all the airborne material is fibrous FBS-1, then a Workplace Exposure Standard (WES) of 2mg/m³ (inhalable dust) applies.</p> <p>An 8-hour time-weighted average (TWA) exposure is the average airborne concentration measured over an eight-hour working day and a 5-day working week, over an entire working life. According to current knowledge, this concentration should not impair the health or cause undue discomfort to nearly all workers.</p>
Engineering controls:	During most applications and installation of this product, no special ventilation will be required.
Personal protection	
Respiratory protection:	None required for this product in usual working conditions. An approved particulate respirator conforming to Australian and New Zealand Standards AS/NZS 1715 and 1716 is recommended if dust from the product is created. Heating of product above 120°C, may cause smoke or fumes, and cartridge-type or powered respirators or supplied-air helmets or suits may be necessary. Use only respirators that bear the Australian Standards mark and are fitted and maintained correctly and kept in clean storage when not in use.
Eye protection:	No specific requirements for this product. Eye protection recommended for work where dust or particles may be generated. See Australian Standards AS 1336 and AS/NZS 1337 for more information.
Skin protection:	Direct skin contact can be minimised by wearing long sleeved shirts and long trousers, a cap or hat, and standard duty gloves. See Australian Standards AS2161 and 2919 and AS/NZS 2210 for more information.
Hygiene Practices:	Not applicable

Section 9: Physical and Chemical Properties

Appearance:	Sheet in roll form
Physical properties:	Roll
Odour:	None
Melting range (°C):	Adhesive softens at 70°C
Boiling range (°C):	Not applicable
Decomposition temperature (°C):	120°C
Volatile Component (% vol):	Not applicable
Solubility in Water (g/L):	Insoluble
pH (as supplied):	Not applicable

Section 10: Stability and Reactivity

Chemical stability:	No reported incompatibilities
Hazardous decomposition products:	Heating to over 120°C will result in toxic fumes (chlorine and hydrogen chloride) being produced.
Hazard Polymerisation:	None known
Conditions to avoid:	Heating to over 120°C

Section 11: Toxicological Information

Inhalation:	None when using product as supplied. Dust may be slightly irritant and fumes from high temperature decomposition may be irritant and cause headaches, nausea and irritation of lungs (see Sections 5 and 8).
Ingestion:	Unlikely under normal conditions of use, but may result in mild irritation of the lips, mouth and throat.
Eye:	Physical irritant only. Dust or fumes from high temperature decomposition may cause eye discomfort resulting in watering and redness.
Skin:	None from handling product as supplied. Dust from cutting or abrading product may cause mild irritation.
Chronic health effects:	No effects from chronic exposures to dust are reported. Antimony Trioxide (production) is regarded as a category 2 carcinogen (suspect human carcinogen) by Safe Work Australia in the list of Atmospheric Contaminants as released in April 2018. Antimony Trioxide itself is not classified as a carcinogen by Safe Work Australia. The Antimony Trioxide in this product (less than 10%) is not classifiable as carcinogenic. Exposure to dust from this product (or fumes from high temperature decomposition) is not known or suspected to be carcinogenic.
Existing conditions aggravated by exposure:	Not applicable

Section 12: Ecological Information

Ecotoxicity:	Sisalkraft® is inert and is not considered to pose any environmental or ecological risk.
Mobility:	No information available

Section 13: Disposal Consideration

Disposal methods and containers:	Dispose according to local and state government regulations.
Special precautions for landfill or incineration:	Please consult your state Land Waste Management Authority for more information.

Section 14: Transportation Information

Transport requirements:	Not regulated for transport of dangerous goods: ADG7, UN, IATA, IMDG
Hazchem code:	Not applicable

Section 15: Regulatory Information

Poisons Schedule:	None
Poisons Information Centre	13 11 26 (Australia Wide)

Section 16: Other Information

Additional Information and Reference Documents

Poisons Information Centre 13 11 26 (Australia Wide)

Please read instructions/label before using product.

Code on Preparation of a Safety Data Sheets for hazardous chemicals, December 2011, Safe Work Australia.

Australian Standards References:

AS/NZS 1336	Recommended practices for occupational eye protection
AS/NZS 1715	Selection, use and maintenance of respiratory protective equipment
AS/NZS 1716	Respiratory protective devices
AS/NZS 2161	Occupational protective gloves selection, use and maintenance
AS2919	Industrial clothing
AS/NZS 2210	Occupational protective footwear

Abbreviations used:

IARC:	International Agency for Research on Cancer
NTP:	National Toxicology Program (U.S.)
OSHA:	Occupational Safety and Health Administration (U.S.)
STEL:	Short term exposure limit
TWA:	Time weighted average

Prepared by: 4cRisk.com.au Pty Ltd

This Safety User Information Sheet (SUIS) was correct at the time it was prepared (see below for the date). The Supplier, as part of its Health and Safety Programme, updates SUIS when its ongoing review process indicates a need for a change to be made. Ensure that the SUIS you are reading and relying on is current. You can do this by contacting the Supplier at the address on page 1.

Issue Date:	31 January 2022
Revision:	1
Supersedes:	SUIS10_Revision_0_Issue Date 310120
Reason for issue:	Update

© Fletcher Insulation Pty Limited 2022. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. The colour PINK, Pink® and Pink® Batts are registered trademarks of Owens Corning used under licence by Fletcher Insulation. FBS-1 Glasswool Bio-Soluble Insulation® is a registered trademark of ICANZ. Unless otherwise stated all ™ and ® are trademarks and registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355. SUIS10_Revision_1_Issue Date 310122.