

## Pink® SonoMatt® Blanket

### Acoustic ceiling overlay

#### Description

Pink® SonoMatt® Blanket comprises of a glasswool insulation blanket with a black, non-woven regina tissue adhered to one side.

#### Applications

Pink® SonoMatt® Blanket may be used in applications such as partitions, screens and baffles. Its black tissue facing makes it ideal for installation behind perforated linings to conceal imperfections and improve the overall acoustic properties of the internal lining. Typically used as a ceiling overlay, Pink® SonoMatt® Blanket provides effective sound absorption and transmission properties particularly for 'problem' acoustic applications which cannot be satisfied with more routine acoustic products. In addition to providing acoustic performance, Pink® SonoMatt® Blanket provides the added benefit of thermal insulation and increases the overall total R-value of a building envelope, thus improving the energy efficiency of a building.

#### Product limitations of use

- Not to be used/exposed to weather in any condition including prior, during and after installation.
- Not suitable for applications where high humidity is present within building (wet climates for a long period).
- This product can not be classified to AS1530.1 as an assembly, and is not suitable where non-combustible material is required.
- This product does not have a group number in accordance with AS 5637.1 and is not suitable for exposed applications where a group number is required.
- Product needs to be allowed to fully recover before installation.
- The facing is not a water or vapour barrier, not to be used where vapour or water control is required.
- Modifications not permissible, as suitability &/or compliance may be compromised.

#### Features and benefits

<b>Codemark certified to AS 4859.1 for thermal performance</b>	→	Assurance that the product meets the requirements of National Construction Code.
<b>Assists in reducing unwanted noise in buildings</b>	→	Provides a more comfortable living and working space.
<b>Delivers overall building energy efficiency keeping buildings cool in summer and warm in winter</b>	→	Reduces future ongoing costs on energy bills and unnecessary stress on HVAC systems.
<b>FBS-1 Bio-Soluble product</b>	→	Safe and comfortable to handle.

### Product data

Material R-value	Thickness mm	Width mm	Length m	m <sup>2</sup> per roll	Old product code	New product code
R1.3	55	1200	20	24	941045	4005597
R1.8	75	1200	15	18	941046	4005598
R2.5	100	1200	15	18	941047	4005599
R3.0	130	1200	12	14.4	941048	4005265

### Physical properties

Property	Test method/standard	Result	Unit
Thermal resistance R-value	AS/NZS 4859.1	Complies	m <sup>2</sup> K/W
Moisture absorption	When exposed to environmental conditions of 50°C and 95% relative humidity for four days	< 0.2	% by volume
Maximum service temperature	ASTM C411/C447	Glasswool: 340 Facing: 70	°C
Fungi resistance of insulation materials	C1338-14	Pass (No growth)	

### Fire hazard properties

Pink® SonoMatt® Blanket exhibits the following characteristics when tested in accordance with the following standards:

Property	Test method/standard	Result
Combustibility (unfaced glasswool component only)	AS/NZS 1530.1	Non-combustible
Early Fire Hazard Indices	AS/NZS 1530.3	
Ignitability Index		0
Spread of Flame Index		0
Heat Evolved Index		0
Smoke Developed Index		2

### Compliance

#### NCC 2019

- Complies with AS/NZS 4859.1 as referenced in NCC 2019, Volume 1 Clause J1.2(a) and NCC 2019, Volume 2 Clause 3.12.1.1.
- When tested to AS/NZS 1530.3 this product does not exceed the 'Spread of Flame' or 'Smoke Developed' indices as required by NCC 2019 Volume 1, Specification C1.10 Clause 7 for insulation materials.

#### NCC 2022

- Complies with AS/NZS 4859.1 as referenced in NCC 2022, Volume 1 Clause J4D3 (1) and NCC 2022, Volume 2 ABCB Housing provisions Clause 13.2.2.
- When tested to AS/NZS 1530.3, this product does not exceed the 'Spread of Flame' or 'Smoke Developed' indices as required by NCC 2022 Volume 1, S7C7 for insulation materials.

### Acoustic performance

#### Flow resistivity

Acoustic performance of Pink® SonoMatt® Blanket products used in sound absorption applications can be measured by their resistance to air flow. This is recognised as flow resistivity. Tested in accordance with ASTM Standard C522-03 Standard Test method for Airflow Resistance of Acoustic Materials. The following table rates the flow resistivity of Pink® SonoMatt® Blanket products:

Product	Material R-Value m <sup>2</sup> K/W	Thickness mm	Flow resistivity RAYLS/m
Pink® SonoMatt® Blanket	R1.3	55	4120
Pink® SonoMatt® Blanket	R1.8	75	4010
Pink® SonoMatt® Blanket	R2.5	100	6610

### Health and safety

Pink® SonoMatt® Blanket insulation is manufactured from FBS-1 Glasswool Bio-Soluble Insulation®. Refer to Fletcher Insulation SUIS for more information.

### Environmental properties

The Glasswool component of Pink® SonoMatt® blanket is manufactured from up to 80% recycled glass which would otherwise go into landfill and be unsuitable for alternative manufacturing processes.

Fletcher Insulation avoids the use of Ozone Depleting Potential (ODP) substances in the manufacture or composition of its FBS-1 Glasswool Bio-Soluble Insulation®.

The use of Pink® SonoMatt® Blanket insulation guarantees the use of Zero ODP insulation while also ensuring that no harmful levels of Volatile Organic Compounds (VOCs) are released. This allows the incorporation of environmentally preferable insulation whilst also maintaining indoor air quality.

### Maintenance and conditions of use

- Product should be kept dry at all times, not to be exposed to weather in any condition including prior, during and after installation.
- Product's facing should not be in contact with any water or alkaline materials such as wet concrete etc.
- Use of pressure cleaners or mineral based cleaners must not be used on the facing product.
- If product is compressed it will reduce the thermal performance of the product, ensure product recovers to its nominal thickness to achieve declared material R-value.
- Where insulation can be inspected, ensure any tears in the facing are repaired with appropriate tape as highlighted in the product's installation guidelines.
- When storing, ensure product is protected from physical damage. Avoid storing product packaging under UV light (direct sunlight) for extended periods.
- When product is installed as per the product installation guidelines, no further maintenance is required for this product.

### Technical specification

**When specifying, please state the following:**

The insulation material must be Fletcher Insulation Pink® SonoMatt® Blanket insulation. The insulation shall achieve a Material R-value of R\_\_\_\_\_m<sup>2</sup>K/W (specify Material R-value) at a nominal thickness of \_\_\_\_\_mm (specify insulation thickness).

**The following performance attributes must be specified:**

- Product must be FBS-1 Biosoluble.
- Product must recover to the requirements of AS/NZS 4859.1.

### Installation instructions

For the correct installation method, follow the Installation Guidelines available from [insulation.com.au](http://insulation.com.au)

© Fletcher Insulation Pty Limited 2024. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. The colour PINK, Pink® and Pink® Batts are registered trademarks of Owens Corning used under licence by Fletcher Insulation. FBS-1 Glasswool Bio-Soluble Insulation® is a registered trademark of ICANZ. Unless otherwise stated all ™ and ® are trademarks and registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355. CTDS4\_Revision\_2\_Issue date 14062024.