

Trade Batts®: Wall

Thermal insulation for residential wall applications

Description

Trade Batts® are made from lightweight, flexible and resilient glasswool for thermal and acoustic insulation of residential walls. Trade Batts® are available in various sizes to fit standard stud spacings.

Applications

Trade Batts® are the trusted choice when it comes to constructing new homes or retrofitting existing buildings for increased thermal efficiency. The Trade Batts® insulation range is available in various thermal R-values and dimensions, ensuring there is an effective and efficient product solution for every application.

Trade Batts®, renowned for their firmness, are low itch, easy to cut and friction-fit standard wall studs to make homes feel cooler in summer, warmer in winter and provide energy savings all year round.

Features and benefits

Firm friction-fit	→	Holds firmly in place once installed to deliver stated thermal performance.
AS/NZ 4859.1:2018 compliant	→	Peace of mind that Trade Batts® meet the BCA requirements.
Made from recycled glass	→	Supporting sustainability and environmentally conscious manufacturing.
Low VOCs	→	Safe to use as no harmful VOCs are released when in use.

Physical characteristics

Material R-value m ² K/W	Nominal thickness mm	Width mm	Length mm	Batts per pack	Area per pack m ²	Coverage per pack m ²	Bag weight kg	Packs per bale	Old product code	New product code
R2.5HD	90	430	1160	14	6.98	7.85	12.57	5	331112	4005312
	90	580	1160	14	9.42	10.60	16.96	5	331113	4005313

Physical properties

Property	Test method/standard	Result	Unit
Maximum service temperature	ASTM C411/C447	350	°C
Thermal resistance	AS/NZS 4859.1	Complies	m ² K/W
Moisture absorption		< 0.2	% by volume
pH	ASTM C871	9 (does not contribute to the corrosion of steel structures)	-

Fire hazard properties

Trade Batts® exhibit the following characteristics when tested in accordance with the following standards:

Property	Test method/standard	Unfaced
Combustibility	AS 1530.1	Non-combustible
Early Fire Hazard Indices	AS/NZS 1530.3	
Ignitability Index		0
Spread of Flame Index		0
Heat Evolved Index		0
Smoke Developed Index		0-1

Environmental properties

Trade Batts® insulation avoids the use of Ozone Depleting Potential (ODP) substances in the manufacture or composition of its Glasswool Bio-Soluble Insulation®.

The use of Trade Batts® insulation products guarantees the use of Zero ODP insulation while also ensuring that no harmful levels of Volatile Organic Compounds (VOCs) are released. This allows the incorporation of environmentally preferable insulation whilst also maintaining indoor air quality.

Health and safety

Glasswool products are manufactured from Glasswool Bio-Soluble Insulation®. It is safe to use and is classified as non-hazardous according to the criteria of Safe Work Australia. Glasswool insulation can be used with confidence in any residential, commercial or industrial application. Bio-soluble fibres have been extensively researched and shown to pose no long term health risks.

Technical specification

When specifying, state the following:

The insulation material shall be Trade Batts® Wall R _____ m2K/W (Material R-value)
 _____ (thickness) x _____ (width) x _____ (length) mm.

© Fletcher Insulation Pty Limited 2024. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. The colour PINK, Pink® and Pink® Batts are registered trademarks of Owens Corning used under licence by Fletcher Insulation. FBS-1 Glasswool Bio-Soluble Insulation® is a registered trademark of ICANZ. Unless otherwise stated all ™ and ® are trademarks and registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355. RTDS13_Revision_1_Issue date 03042024.