

Sisalation® Multipurpose EHD (456)

Description

Sisalation® Multipurpose EHD (456) is an extra heavy duty, non-vapour permeable single sided reflective aluminium foil and polyweave laminate. This product has an antiglare face designed to minimise glare experienced during installation.

Application

Sisalation® Multipurpose EHD (456) is designed for use as a pliable building membrane in applications such as brick veneer walls, tile roofs (with the exception of slate) and residential and commercial metal roofs. Sisalation® Multipurpose products are specifically designed for external wall applications in climate zones 1-3 and in suitable roofing applications in all climate zones.

When overlapped and sealed with Vapastop® 883 Reinforced Foil Tape, Sisalation® Multipurpose products provide a tough secondary skin for vapour and moisture control and act as a wind, heat and dust barrier. This effective barrier also protects the building frame by minimising the amount of rain and dust that penetrates.

Product limitations

- **Important: Do Not Modify This Product:** Compliance with the evidence of suitability data referenced in this document is only achieved by the product or configuration listed.
- This product does not have a group number in accordance with AS 5637:1 and is not suitable in exposed internal wall or ceiling lining applications.
- This product is not suitable for wall applications where a vapour permeable, pliable building membrane is required per NCC Volume 1 & 2 or where the cladding manufacturer specifies a vapour permeable membrane.
- Additional mechanical fasteners may be required for product exposed to adverse weather conditions. Product must be inspected for damage and repaired/replaced prior to cladding being installed.


Features and benefits

Extra Heavy Duty product	→	Suitable for use in both residential and commercial projects.
Vapour and water barrier	→	Class 1 Vapour Barrier and Water Barrier.
Anti-glare face	→	Reduces glare during installation.

Product data

Width mm	Length m	Area per roll m ²	Weight per roll kg	Old product code	New product code
1350	30	40.50	4.66	352330	4006736
1350	60	81.00	9.32	352360	4006738
1500	30	45.00	5.12	352331	4006737

Product composition



Physical properties

Property		Test method/Standard	Test result	Unit
Duty Classification		AS/NZS 4200.1	Extra Heavy Duty	
Edge Tear	Machine	TAPPI T470	≥ 90	N
	Lateral		≥ 90	N
Tensile Strength	Machine	AS 1301.448s	≥ 13.0	kN/m
	Lateral		≥ 10.5	kN/m
Water Control		AS/NZS 4201.4	Water Barrier	
Vapour Control		AS/NZS 4200.1	Class 1 Vapour Barrier	
Vapour Permeance		ASTM E96	<0.0022	µg/N.s
Air Control		ISO 5636-5	Air Barrier (>0.1)	MNs/m ³
Emittance	Anti-glare face	AS/NZS 4201.5	IR Non-reflective (0.9)	
	Silver side		IR Reflective (≤0.05)	
Resistance to Dry Delamination		AS/NZS 4201.1	PASS	
Resistance to Wet Delamination		AS/NZS 4201.2	PASS	
Shrinkage		AS/NZS 4201.3	≤ 0.5	%
Electrical Conductivity		AS/NZS 3100	Electrically Conductive	
Nominal Thickness			< 1.0	mm

Fire hazard properties

Sisalation® Multipurpose EHD (456) exhibits the following characteristics when tested in accordance with the following standards:

Property	Test method/Standard	Result
Flammability Index	AS/NZS 1530.2	≤5 (Low)
BAL Compliance	AS 3959	Roof: Low-40 Wall: Low-FZ

Compliance

NCC 2019

Sisalation® Multipurpose products comply with the National Construction Code (NCC) for sarking type materials and satisfy the following requirements:

- AS 4200.1 for 'Pliable Building Membranes' Deemed to Satisfy Standard, recognised by NCC Volumes 1 and 2.
- Meets the requirements of NCC 2019 Volume 1 F6.2(a) & Volume 2 3.8.7.2(a) through compliance with AS 4200.1
- NCC 2019 Volume 1 Non-Combustible building elements C1.9(e) (vi) Sarking-type materials that do not exceed 1mm in thickness and have a Flammability Index not greater than 5. NCC 2019 Volume 2 General Concession – Non-Combustible Materials 3.7.1.1 (f) Sarking-type materials that do not exceed 1mm in thickness and have a Flammability Index not greater than 5.
- When tested to AS/NZS 1530.2 this product does not exceed the 'Flammability index' as required by NCC 2019 Volume 1, Specification C1.10 Clause 7 for Sarking-Type materials: In other locations.
- Suitable for use in bushfire areas with a Bushfire Attack Level (BAL) Low-FZ (wall) or Low-40 (roof) in accordance with AS 3959.

NCC 2022

- AS 4200.1 for 'Pliable Building Membranes' Deemed to Satisfy Standard, recognised by NCC Volumes 1 and 2. Meets the requirements of NCC 2019 Volume 1 F8D3 & Housing Provisions 10.8.1 through compliance with AS 4200.1
- Product meets non-combustible exemption for sarking type material outlined in NCC 2022 Volume 1 Non-Combustible building elements C2D10(6)(f) Sarking-type materials that do not exceed 1mm in thickness and have a Flammability Index not greater than 5.
- NCC 2022 Volume 2 General Concession – Non-Combustible Materials H3D2(1) (f) Sarking-type materials that do not exceed 1mm in thickness and have a Flammability Index not greater than 5.
- When tested to AS/NZS 1530.2 this product does not exceed the 'Flammability index' as required by NCC 2022 Volume 1, S7C7 for Sarking-Type materials: In other locations.
- Suitable for use in bushfire areas with a Bushfire Attack Level (BAL) Low-FZ (wall) or Low-40 (roof) in accordance with AS 3959.

Environmental properties

Fletcher Insulation avoids the use of Ozone Depleting Potential (ODP) substances in the manufacture or composition of its FBS-1 Glasswool Bio-Soluble Insulation® and Sisalation® reflective foil products.

The use of Sisalation® pliable building membranes guarantees the use of zero ODP insulation while also ensuring that no harmful levels of Volatile Organic Compounds (VOCs) are released. This allows the incorporation of environmentally preferable insulation whilst also maintaining indoor air quality.

Maintenance and conditions of use

- Use of pressure cleaners or mineral based cleaners must not be used on the foil facing product.
- Where Sisalation® Pliable Building Membranes can be inspected, ensure any tears are repaired with appropriate tape, such as Vapastop® 883 Foil Tape.
- When storing, ensure product is protected from all physical damage at all times. Avoid storing product packaging under UV light (direct sunlight) for extended periods.
- Sisalation® Pliable Building Membranes products must be kept dry at all times, out of contact with direct sunlight and out of contact with alkaline products, cement and mortar as well as corrosive environments such as chlorine.
- Sisalation® Pliable Building Membranes products are not designed to withstand weathering hence the external cladding should be applied without delay.
- Products exposed to harsh weather conditions prior to cladding must be inspected for damage and repaired or replaced to ensure compliance with the Product Warranty.
- Sisalation® Pliable Building Membranes shall be installed in accordance with AS/NZS 4200.2 'Pliable Building Membranes and Underlays – Installation Requirements for Metal Roofs, Tile Roofs and Walls'
- Building Designer to consider the suitability of this product based on the projects design requirements.

Health and safety

There are no known health or safety risks associated with this product for applications described in this datasheet. Sisalation® Multipurpose EHD (456) contains aluminium foil and can conduct electricity. To avoid electrocution, care should be taken to ensure products do not come into contact with electrical wiring during installation or use. For additional information or to request a Safety Use Information Sheet please visit www.insulation.com.au or contact your Fletcher Insulation Representative.

Technical specification

When specifying, please state the following:

The pliable building membrane shall be Fletcher Insulation Sisalation® Multipurpose EHD (456)
_____ width mm x _____ length mm, Product Code _____ or approved equal.

The product must have the following properties:

- Classified Extra Heavy Duty
- Vapour permeability <0.0022
- Vapour permeability classification – Class 1
- Classified as a Water Barrier

© Fletcher Insulation Pty Limited 2026. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. The colour PINK, Pink® and Pink Batts® are registered trademarks of Owens Corning Intellectual Capital, LLC used under licence by Fletcher Insulation. FBS-1 Glasswool Bio-Soluble Insulation® is a registered trademark of ICANZ. Unless otherwise stated, all ™ and ® are trademarks and registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355. FTDS7_Revision_8_ Issue Date 23022026.